

YUKON Series

Half-Cell Monofacial Module

540-555Wp | **21.48%**
 Module Power Output | Max Efficiency



Key Features



High module conversion efficiency



Better temperature coefficient



Super multi busbar technology



Low attenuation long warranty



Superior load capacity



Aesthetic appearance




USA based liability insurance



Houston, Texas based company

Warranty



15 <Years> Guarantee on product material and workmanship

25 <Years> Linear power output warranty

Product Certification

IEC61215:2016; IEC 61730:2016; UL61730

IEC62804 PID

IEC61701 Salt Mist

IEC62716 Ammonia Resistance

IEC60068 Dust and Sand

IEC61215 Hailstone

Fire Type (UL61730):Type1

ISO14001:2015; ISO9001:2015; ISO45001:2018



About SEG Solar

SEG Solar is a leading manufacturer of high-performance solar panels for residential, commercial, and utility applications. The company, headquartered in Houston, Texas, is committed to providing cost-effective and reliable solar solutions that help customers reduce their energy costs and carbon footprint.



Download Datasheet

YUKON Series SEG-XXX-BMA-HV(144Cells)

Electrical Characteristics

Module Type	SEG-540-BMA-HV		SEG-545-BMA-HV		SEG-550-BMA-HV		SEG-555-BMA-HV	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power -Pmp(Wp)*	540	406	545	409	550	414	555	418
Open Circuit Voltage -Voc(V)	49.50	46.18	49.60	46.32	49.70	46.40	49.80	46.50
Short Circuit Current -Isc(A)	13.81	11.16	13.91	11.23	14.01	11.32	14.10	11.41
Maximum Power Voltage -Vmp(V)	41.55	38.39	41.81	38.41	42.07	38.58	42.31	38.68
Maximum Power Current -Imp(A)	13.00	10.59	13.04	10.65	13.08	10.73	13.12	10.81
Module Efficiency(%)	20.90		21.10		21.29		21.48	
Power Tolerance(W)	(0, +4.99)							
Maximum System Voltage	1500V DC							
Maximum Series Fuse Rating	25 A							

STC: Irradiance 1000 W/m² module temperature 25°C AM=1.5

NOCT: Irradiance 800W/m² ambient temperature 20°C module temperature 45°C wind speed: 1m/s

*Measuring tolerance: ±3%

Mechanical Specifications

External Dimension	2278 x 1134 x 35 mm
Weight	27.0 kg
Solar Cells	PERC Mono 182 x 91mm(144 pcs)
Front Glass	3.2mm AR coating tempered glass / low iron
Frame	Anodized aluminium alloy
Junction Box	IP68 / 3 diodes
Connector Type	PV-CO02-xy
Cable Type	12 AWG PV Wire (UL)
Cable Length	Portrait: 400 mm(+)/ 200 mm(-) Landscape: 1200 mm(+)/ 1200 mm(-) or customized length
Mechanical Load(Front)	5400 Pa / 113 psf*
Mechanical Load(Rear)	2400 Pa / 50 psf*

*Refer to SEG installation Manual for details

Packing Configuration

Container	20'GP	40'HQ
Pieces per Pallet	31	31
Pallets per Container	4	20
Pieces per Container	124	620


Temperature Characteristics

Pmax Temperature Coefficient	-0.35 %/°C
Voc Temperature Coefficient	-0.27 %/°C
Isc Temperature Coefficient	+0.05 %/°C
Operating Temperature	-40~+85 °C
Nominal Operating Cell Temperature (NOCT)	45±2 °C

www.segsolar.com

Specifications subject to technical changes SEG_DS_EN_2023V4.0 © Copyright 2023 SEG Solar

Technical Drawing



*Refer to SEG installation Manual for details

I-V Curve

